Axle Rating 3 Trailer Weight Overall Width Overall Length Loading Surface Area Deck Surface Tre Lifting Device Hydrauli Suspension Single	,	U-12 4,500 lbs.	U-14 10,000 lbs.	U-19 10.000 lbs.	U-24 15.000 lbs.	U-24GN
Maximum Payload Axle Rating 3 Trailer Weight Overall Width Overall Length Loading Surface Area Deck Surface Lifting Device Suspension Single	1,950 lbs.	4,500 lbs.				
Axle Rating 3 Trailer Weight Overall Width Overall Length Loading Surface Area Deck Surface Tree Lifting Device Hydrauli Suspension Single	,	,	10,000 lbs.	10.000 lbs.	15 000 lbs	
Trailer Weight Overall Width Overall Length Loading Surface Area Deck Surface Tre Lifting Device Hydrauli Suspension Single	3,500 lbs. 1 :	7000 11			15,000 153.	15,000 lbs.
Overall Width Overall Length Loading Surface Area Deck Surface Tre Lifting Device Hydrauli Suspension Single		x 7,000 lbs.	2 x 7,000 lbs.	2 x 7,000 lbs.	3 x 7,000 lbs.	3 x 7,000 lbs.
Overall Length Loading Surface Area Deck Surface Tre Lifting Device Hydrauli Suspension Single	1,050	2,100	3,600	4,000	5,400	6,000
Loading Surface Area Deck Surface Tre Lifting Device Hydrauli Suspension Single	94"	82"	102"	102"	102"	102"
Deck Surface Tree Lifting Device Hydrauli Suspension Single	14′	18'6"	19'6"	23'8"	27′	32′7″
Lifting Device Hydrauli Suspension Single	72" x 9'	0" x 10'10"	80" x 14'	80" x 18'	80" x 20'8"	80" x 20'8"
Suspension Single	eated Pine Tr	reated Pine	Treated Pine	Treated Pine	Hardwood	Hardwood
1	lic w/ Elec. Assist Hydrau	ilic w/ Elec. Assist Hydr	raulic w/ Elec. Assist H	ydraulic w/ Elec. Assist H	lydraulic w/ Elec. Assist Hy	ydraulic w/ Elec. Assist
	e Axle Torsion Single	e Axle Torsion Tw	vin Axle Torsion	Twin Axle Torsion	Tri-Axle Torsion	Tri-Axle Torsion
Electric Brakes	Optional	Standard	Standard	Standard	Standard	Standard
Wheel Size	14"	16"	16"	16"	16"	16"
Hitch Size	2"	2 - 5/16"	2 - 5/16"	2 - 5/16"	Pintle	Gooseneck
Systems & Storage Box	Standard	Standard	Standard	Standard	Standard	Standard
Lighting	LED	LED	LED	LED	LED	LED
Welded D-Rings	N/A	4	6	6	6	6
Tie Down Chain Key Slots	- (4) 2/5	Side-Frt & Rear (4) 2	2/Side-Frt & Rear (4	4) 2/Side-Frt & Rear (4	4) 2/Side-Frt & Rear (4	4) 2/Side-Frt & Rear
Battery	Group 31	Group 31	Group 31	Group 31	Group 31	Group 31
Stake Bed Pockets S	Standard	Standard	Standard	Standard	Standard	Standard
Safety Lock						6: 1 1
Warranty	N/A	Standard	Standard	Standard	Standard	Standard

ELIMINATE INJURIES! SAVE TIME & MONEY! AVOID EQUIPMENT DAMAGE

FEATURES & BENEFITS

NO RAMP ADVANTAGES

- Eliminate injuries caused by heavy ramps such as pulled back muscles, smashed feet, and severed fingers that lead to worker comp claims or law suits.
- Save time & money as loading/unloading can be done with-or-without tow vehicle being attached.
- Avoid equipment damage as low approach angle protects equipment from damage caused by falling off ramps during loading and unloading.

LOW APPROACH ANGLE

- Ability to load any low clearance equipment quickly and safely due to low approach angle.
- Applications: Skid Steers, Scissor Lifts, Fork Lifts, Construction, Farming, Industrial Cleaning Equipment, plus so much more...

TORSION AXLE

Superior ride and long life

LED RUBBER MOUNTED LIGHTING

 Better visibility for safety, and low voltage draw for battery life.

ADJUSTABLE COUPLER

Allows for any truck in the fleet to do the towing.

AUXILIARY RECEIVER

Used for winch mount and other needs.

EASY ACCESS GREASE ZERKS

Deck side grease zerks for axle pins, and fender hinges.

FACTORY MOLDED WIRE HARNESS

All connections use molded components for long life operation

NO JACK NEEDED FOR TIRE CHANGES

 Reduces time with added safety. Break lug nuts loose, apply blocks under each rear corner of trailer, and lower unit to raise tires off the ground.

BUILT-IN THEFT PREVENTION

 Frees up time and reduces theft exposure Lower trailer, lock it, and leave it!

LOCKING MECHANISM

 For assured safety of load, in case of accidental hydraulic line damage.

STAKE BED POCKETS WITH RUB RAIL

 Provides additional tie down locations, framing-or-racking opportunity, and added main frame strength.

15' EXTENSION CORD CONTROL MODULE

Allows for activation of trailer at the systems box, or up to 15` away.

OPTIONS AVAILABLE FOR ALL MODELS

- Custom Colors
- Military CARC Coating
- Wireless Remote Key Fob
- Spare Tire
- Spare Tire Rack
- Aluminum Custom Wheels
- Mobile D-Rings
- Trailer Deck Mounted Receiver
- Pintel Hitch
- Winch Plate
- Winch
- Solar Trickle Charger
- 10amp On-Board Battery Charger
- Hardwood Decking
- Diamond Plate Steel Decking
- Electric/Hydraulic Jack Stand
- Drum Surge Brakes

Visit NoRamp.com to See NoRamp in Action











ELIMINATE INJURIES! SAVE TIME & MONEY! AVOID EQUIPMENT DAMAGE!

